PHILLIPS MANUFACTURING CO.
Engineered to Perform

Submittal Form

EDGE*master*® 2-1/2” Starter Strip

2-1/2” Starter Strip is used as a permanent siding part. Starter strip, as the name implies, is the first part installed when putting permanent siding onto a home. It is installed level and at the lowest point of the original sheathing. This gives the first row of siding something to hook on to. If the starter strip is not installed level to the eave, the siding will appear to go up or down hill. This product is only available in hot-dipped galvanized finish.

Drawing not to scale

Product Data and Ordering Information

Material: .0.012 min thickness, G30 galvanized
Part Number: SS250-28HDG

Length	Pieces Per Bundle	Bundles Per Pallet	Feet Per Bundle
10”	25	35	250

All Phillips products are made in the U.S.A.

ASTM and Code Standards

Phillips Roofing Metals meets or exceeds:

- ASTM A 653 Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process
- SMACNA Residential Sheet Metal Guidelines 2001

SDS and other technical information available at www.phillipsmfg.com.

Leed Credits for Recycled Content

MR2 – The steel and vinyl used in Phillips Manufacturing products is 100% recyclable.
MR4 – Phillips Manufacturing steel and vinyl products have a minimum of:

Total recycled content:	30%
Post-consumer recycled content:	25%
Pre-consumer recycled content:	5%

Storage

Avoid bending or other damage and store in a dry place protected from moisture.

©2015 Phillips Manufacturing Company