

## EDGEmaster® 3/4" Offset Starter Strip

3/4" Offset Starter Strip is used as a permanent siding part. Starter strip, as the name implies, is the first part installed when putting permanent siding onto a home. It is installed level and at the lowest point of the original sheathing. This gives the first row of siding something to hook on to. The 3/4" offset is used when 3/4" insulation is installed after the starter strip. If the starter strip is not installed level to the eave, the siding will appear to go up or down hill. This product is only available in hot-dipped galvanized finish.



### Product Data and Ordering Information

Material: .012 min thickness, G30 galvanized  
Part Number: SS750S-28HDG

Length	Pieces Per Bundle	Bundles Per Pallet	Feet Per Bundle
10"	25	35	250

All Phillips products are made in the U.S.A.

### ASTM and Code Standards

Phillips Roofing Metals meets or exceeds:

- ASTM A 653 Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process
- SMACNA Residential Sheet Metal Guidelines 2001

SDS and other technical information available at [www.phillipsmfg.com](http://www.phillipsmfg.com).

### Leed Credits for Recycled Content


MR2 – The steel and vinyl used in Phillips Manufacturing products is 100% recyclable.

MR4 – Phillips Manufacturing steel and vinyl products have a minimum of:

Total recycled content:	30%
Post-consumer recycled content:	25%
Pre-consumer recycled content:	5%

### Storage

Avoid bending or other damage and store in a dry place protected from moisture.



*Drawing not to scale*